

**UMP 1 L-Power dual, clay plaster machine**

230 V/400 V, 16 A, switchable

application:

loam plaster machine, mixing pump, plastering machine, concrete pump, conveying pump

manufacturer: Deutsche Foerdertechnik

technical data

possible pumping capacities:	6 – 35 litres/min with D-pumps 35 – 65 litres/min with R-pumps
working pressure max.:	max. 30 bar
conveying distance max. with diameter 25 mm:	25 m with plaster
conveying distance max. with diameter 35 mm:	35-40 m with plaster 50 m with calcium sulphate floor screed
working pressure max. :	30 bar
drive:	4 kW, 230 V / 400 V, 50 Hz, switchable
power supply:	230 V/400 V, 16 A slow-blow fuse
power cable:	5 x 2,5 mm ² , 25 m or 5 x 4,0 mm ² , 50 m (extra accessories)
fuse protection:	1 x 16 A + 1 x 10 A 3 x 16 A slow-blow fuse
water supply connection:	3/4 " with Geka-coupling
water pressure in operation :	min. 2,5 bar
remote control:	via air or control voltage
mortar pressure hose:	standard d = 25 mm (NW25) on request d = 35 mm (NW35)
filling height:	730 mm
material container content:	115 litres
length / width / height:	1710 / 650 / 8100 mm
total weight:	157 kg

**UMP 1 L-Power, clay plaster machine**

230 V/400 V, 16 A, switchable

application:

loam plaster machine, mixing pump, plastering machine, concrete pump, conveying pump

manufacturer: Deutsche Foerdertechnik

standard equipment**standard equipment loam plaster machine UMP 1 L-Power dual
230 V/400 V, 16 A with 4,0 kW-pump**

with 4,0 kW motor complete with:
pump unit D 6 3 maintenance-free standard
geared motor 4,0 kW
mixing shaft standard
dosing shaft variant 5 f. L-Power
water flow meter 100-1000 l/h
air compressor with pressure switch-off
adapter for a separate circuit
for air compressor in 230-V-mode
mixing zone
fine plaster spraying gun
connector for remote control
mortar pressure hose 25 mm,
length 10 m, cpl. with couplings
water / air hose 1/2",
length: 10 m, cpl. with couplings
mortar pressure
tool bag
operating instructions